



COMPACT HYDRAULIC SHEARS

MODEL SHOWN: HS-5210C

MODEL		HS-5214C	HS-5210C	HS-6014C	HS-6010C	HS-8014C
Cutting Capacity	Mild Steel	2.0 X 1320 mm 14 GA. x 51"	3.5 x 1320 mm 10 GA. x 51"	2.0 x 1550 mm 14 GA. x 61"	3.5 x 1550 mm 10 GA. x 61"	2.0 x 2050 mm 14 GA. x 80"
	Stainless Steel	1.2 X 1320 mm 19 GA. x 51"	2.3 X 1320 mm 13 GA. x 51"	1.2 X 1550 mm 19 GA. x 61"	2.3 X 1550 mm 13 GA. x 61"	1.2 x 2050 mm 19 GA. x 80"
Strokes Per Minute (SPM)		35	28	30	26	26
Front Support		600 mm 23 5/8"	600 mm 23 5/8"	600 mm 23 5/8"	600 mm 23 5/8"	600 mm 23 5/8"
Back guage		600 mm 23 5/8"	600 mm 23 5/8"	600 mm 23 5/8"	600 mm 23 5/8"	600 mm 23 5/8"
Cutting Angle		1°	1°	1°	1°	1°
Motor		3 HP	5 HP	3 HP	5 HP	3 HP
Shipping Weight		1720 lbs	2645 lbs	2210 lbs	3065 lbs	2580 lbs
Approx Size		76" x 34" x 54"	76" x 36" x 58"	86" x 36" x 54"	86" x 36" x 58"	107" x 38" x 56"

MODEL		HS-8010C	HS-10014C	HS-10010C	HS-12014C	HS-12010C
Cutting Capacity	Mild Steel	3.5 X 2050 mm 10 GA. x 80"	2.0 X 2540 mm 14 GA. x 100"	3.5 X 2540 mm 10 GA. x 100"	2.0 X 3100 mm 14 GA. x 122"	3.5 X 3100 mm 10 GA. x 122"
	Stainless Steel	2.3 X 2050 mm 13 GA. x 80"	1.2 X 2540 mm 19 GA. x 100"	2.3 X 2540 mm 13 GA. x 100"	1.2 X 3100 mm 19 GA. x 122"	2.3 x 3100 mm 13 GA. x 122"
Strokes Per Minute (SPM)		24	22	22	20	20
Front Supporter		600 mm 23 5/8"	600 mm 23 5/8"	600 mm 23 5/8"	600 mm 23 5/8"	600 mm 23 5/8"
Back guage		600 mm 23 5/8"	600 mm 23 5/8"	600 mm 23 5/8"	600 mm 23 5/8"	600 mm 23 5/8"
Cutting Angle		1°	2°	2°	2°	2°
Motor		5 HP	5 HP	7.5 HP	5 HP	7.5 HP
Shipping Weight		3820 lbs	4920 lbs	5955 lbs	6175 lbs	7055 lbs
Approx size		107" x 38" x 58"	125" x 40" x 60"	129" x 44" x 60"	151" x 44" x 60"	151" x 44" x 60"

All Specifications & design are subject to change without prior notice

Compact Hydraulic Shears Features

- 1 High carbon, high chrome alloy-tool steel blades
- 2 Front finger guard
- 3 Manual back gauge 600mm
- 4 Front supporting arm
- 5 Side gauge on worktable
- 6 Spring actuated hold downs ensure even pressure (Excluding P-10010 & P-12010)
- 7 Hydraulic hold down system for P-12010 & P-10010 to clamp workpiece tightly
- 8 Full hydraulic system and safety overload protection system (Hydraulic shear only)

OPTIONAL ACCESSORIES

- 1 CE conformity
- 2 Angle Gauge
- 3 NC power back gauge 800 mm with M15S controller
- 4 Hydraulic or Pneumatic sheet supporter

Hydraulic Standard / Optional Features



PRECISION IS KEY

Depend on Us Because COLDWORKS

ORDER NOW 903.663.8500



Coldworksequipment.com